

5

# BIFURCATED AXIALLY FLEXIBLE STENT

## Cross Reference

This application is a continuation-in-part of Serial  
No. 09/028,383, filed February 24, 1998, which is a  
continuation-in-part and claims priority from U.S.  
Application Serial No. 08/934,974, filed September 22,  
1997. Serial No. 08/934,974 claims priority from U.S.  
Application Serial No. 60/010,686, filed January 26, 1996,  
now abandoned; and U.S. Application Serial No. 60/017,479,  
filed April 26, 1996, now abandoned; and U.S. Application  
Serial No. 60/017,415 filed May 8, 1996; and U.S.  
Application Serial No. 60/024,110, filed August 16, 1996;  
and U.S. Application Serial No. 08/770,236, filed December  
20, 1996, all such patent applications of which are  
incorporated herein by reference.

## Field of the Invention

Generally, this invention relates to balloon  
catheters. More specifically, this invention relates to  
balloon catheters used for stent delivery. Most  
specifically, this invention relates to balloon catheters  
useful for delivering bifurcated stents. In particular,  
this invention relates to balloon catheters, which deliver  
stents to an arterial bifurcation.

5

Background of the Invention

10

15

A stent is commonly used as a tubular structure left inside the lumen of a duct to relieve an obstruction. Commonly, stents are inserted into the lumen in a non expanded form and are then expanded autonomously (or with the aid of a second device *in situ*. A typical method of expansion occurs through the use of a catheter mounted angioplasty balloon which is inflated within the stenosed vessel or body passageway in order to shear and disrupt the obstructions associated with the wall components of the vessel and to obtain an enlarged lumen.

20

25

In the absence of a stent, restenosis may occur as a result of elastic recoil of the stenotic lesion. Although a number of stent designs have been reported, these designs have suffered from a number of limitations. These include restrictions on the dimension of the stent such as describes a stent which has rigid ends (8mm) and a flexible median part of 7-21mm. This device is formed of multiple parts and is not continuously flexible along the longitudinal axis. Other stent designs with rigid segments and flexible segments have also been described.

30

Other stents are described as longitudinally flexible but consist of a plurality of cylindrical elements connected by flexible members. This design has at least one important disadvantage, for example, according to this design, protruding edges occur when the stent is flexed around a curve raising the possibility of inadvertent

5 retention of the stent on plaque deposited on arterial walls. This may cause the stent to embolize or move out of position and further cause damage to the interior lining of healthy vessels. (See Figure 1(a) below).

10 Thus, stents known in the art, which may be expanded by balloon angioplasty, generally compromise axial flexibility to permit expansion and provide overall structural integrity.

15 Catheter balloons and medical devices incorporating them are well known for use in the surgical arena. For instance, during angioplasty, stenoses and/or obstructions in blood vessels and other body passageways are altered, in order to increase blood flow through the obstructed area of the blood vessel. For example, in a typical  
20 balloon angioplasty procedure, a partially occluded lumen is enlarged through the use of a balloon catheter that is passed percutaneously by way of the arterial system by way to the site of the vascular obstruction. The balloon is  
25 then deflated to dilate the vessel lumen at the site of the obstruction.

30 Furthermore, another typical procedure uses a "scaffolding," or stent placed on the balloon angioplasty catheter for similar delivery through the arterial system to the site of a vascular obstruction. Thereafter, the balloon angioplasty catheter is inflated, thereby expanding the stent placed on the catheter. When the stent expands, it similarly expands the lumen so that

5 after removal of the deflated catheter, the stent is  
retained in its expanded position and thereby holds open  
that formerly obstructed area of the body passageway.

10 Essentially, a balloon catheter is a thin, flexible  
length of tubing having a small inflatable balloon at a  
desired location along its length such as at or near its  
tip. Balloon catheters are designed to be inserted into a  
body passageway such as the lumen of a blood vessel, a  
15 passageway in the heart, a urological passageway, and the  
like. Typically, the passage of the balloon catheter into  
the body passageway is done with guidance, such as x-ray  
or fluoroscopic guidance.

20 In practice, stent delivery is quite complex. That  
is, a stent is sometimes required to be placed in a rather  
tortuous area of the vasculature. In this instance, it is  
often necessary to have a catheter which is capable of  
negotiating tight turns, and/or being placed along a  
bifurcated length of blood vessel. In some instances,  
25 while a generally occluded section of blood vessel can  
readily be stented, it is often difficult to place a  
second stent at the other portion of a bifurcation. In  
other words, one can imagine the bifurcation as an  
inverted letter "Y" within the body. (The approach of the  
30 catheter concerning this inverted "Y" shape is generally  
through one of the legs in the "Y".) Therefore, the  
balloon passes both between the leg and the trunk or base  
of the "Y" rather readily. However, once a stent is  
placed along these two legs, it is rather difficult to

TOP SECRET

5 place a second stent at or near the junction of the first  
leg and the base of the letter "Y". Of course, the same  
can hold true when the approach is via the base of the "Y"  
and delivery of the first stent is to one of the legs.  
This is all the more true because as one advances through  
10 the vasculature, the arterial sizes go from quite large  
(greater than 1cm diameter) to rather small (some time  
less than 2.5 mm diameter).

15 It would be desirable, therefore, to create a system  
which allows for delivery of a single stent or pair of  
stents at a bifurcation in the vasculature. It would  
further be desirable for this stent or for this delivery  
system to be able to negotiate the bends of the  
bifurcation, and moreover, to provide for easy access when  
20 one stent is already placed. Furthermore, it would be  
quite useful in order to be able to apply the second  
stent, for the first stent to be reliably placed every  
time so that the user knows exactly where the bifurcation  
is located, and as well where the stent must be  
25 appropriately oriented in order to readily access the  
second leg of the "Y" of the bifurcation.

30 Finally, it would be useful for a device such as a  
desired delivery system to carry a stent capable of  
allowing secondary access to a bifurcated portion of the  
vasculature. Thus, it would be most desirable for the  
device to comprise a catheter capable of balloon delivery  
of a stent at a bifurcation, and also balloon delivery of  
a second stent at the bifurcation.

5        Summary of the Invention

10        The present invention overcomes some perceived shortcomings of prior art stents by providing a stent with axial flexibility. In a preferred embodiment, the stent has a first end and a second end with an intermediate section between the two ends. The stent further has a longitudinal axis and comprises a plurality of longitudinally disposed bands, wherein each band defines a generally continuous wave along a line segment parallel to the longitudinal axis. A plurality of links maintains the bands in a tubular structure. In a further embodiment of the invention, each longitudinally disposed band of the stent is connected, at a plurality of periodic locations, by a short circumferential link to an adjacent band. The wave associated with each of the bands has approximately the same fundamental spatial frequency in the intermediate section, and the bands are so disposed that the waves associated with them are spatially aligned so as to be generally in phase with one another. The spatially aligned bands are connected, at a plurality of periodic locations, by a short circumferential link to an adjacent band.

20  
25  
30        In particular, at each one of a first group of common axial positions, there is a circumferential link between each of a first set of adjacent pairs of bands.

      At each one of a second group of common axial positions, there is a circumferential link between each of

5 a second set of adjacent rows of bands, wherein, along the  
longitudinal axis, a common axial position occurs  
alternately in the first group and in the second group,  
and the first and second sets are selected so that a given  
band is linked to a neighboring band at only one of the  
10 first and second groups of common axial positions.

In a preferred embodiment of the invention, the  
spatial frequency of the wave associated with each of the  
bands is decreased in a first end region lying proximate  
15 to the first end and in a second end region lying  
proximate to the second end, in comparison to the spatial  
frequency of the wave in the intermediate section. In a  
further embodiment of the invention, the spatial frequency  
of the bands in the first and second end regions is  
20 decreased by 20% compared with the spatial frequency of  
the bands in the intermediate section. The first end  
region may be located between the first end and a set of  
circumferential links lying closest to the first end and  
the second end region lies between the second end and a  
25 set of circumferential links lying closest to the second  
end. The widths of corresponding sections of the bands in  
these end regions, measured in a circumferential  
direction, are greater in the first and second end regions  
than in the intermediate section. Each band includes a  
30 terminus at each of the first and second ends and the  
adjacent pairs of bands are joined at their termini to  
form a closed loop.

5 In a further embodiment of the invention, a stent is  
provided that has first and second ends with an  
intermediate section therebetween, the stent further  
having a longitudinal axis and providing axial  
flexibility. This stent includes a plurality of  
10 longitudinally disposed bands, wherein each band defines a  
generally continuous wave having a spatial frequency along  
a line segment parallel to the longitudinal axis, the  
spatial frequency of the wave associated with each of the  
bands being decreased in a first end region lying  
15 proximate to the first end and in a second end region  
lying proximate to the second end, in comparison to the  
spatial frequency of the wave in the intermediate section;  
and a plurality of links for maintaining the bands in a  
tubular structure. The first and second regions have been  
20 further defined as the region that lies between the first  
and second ends and a set of circumferential links lying  
closest to the first end and second end.

25 In a further embodiment the widths of the sectionals  
of the bands, measured in a circumferential direction, are  
greater in the first and second end regions than in the  
intermediate section.

30 In yet an additional embodiment, the stent is divided  
into a group of segments, and each of the segments are  
connected by a flexible connector. In addition, the stent  
segments are provided with enhanced flexibility at the  
flexible connectors, due to the geometrical configuration  
of the flexible connectors.



5 Furthermore, the current stent can be modified to  
provide for bifurcated access, whereas the stent itself is  
uniform throughout. If the manufacturer designs such a  
stent to have an essential opening, then it is possible to  
place the stent such that a pair of stents can be placed  
10 one through the other. In this fashion, the stents are  
capable of being placed at a bifurcation, without any  
welding or any special attachments. The interlocking  
mechanism can be incorporated into the stent design to  
cause the stent to interlock at the desired position  
15 during assembly of the device.

In practice, therefore, the current catheter device  
consists of a balloon catheter which comprises a shaft  
portion having a proximal and a distal end. The shaft  
20 portion has a guidewire lumen therethrough. The lumen has  
a proximal opening and a distal opening. The distal  
opening of the shaft portion is located at the distal end  
of the shaft. A balloon is connected to the shaft at the  
shaft distal end. The balloon has proximal and distal  
25 ends and a first guidewire lumen through it. The balloon  
guidewire is in fluid communication with the guidewire  
lumen of the shaft and the first balloon guidewire lumen  
also has proximal and distal ends. The balloon has a  
second guidewire lumen, the second guidewire lumen  
30 containing a distal opening located proximal to the distal  
opening of the first guidewire lumen.

Further, there is disclosed a method of stent  
placement which comprises first guiding a guidewire

5 through the vasculature. Second, a balloon catheter which  
contains two guidewire lumens is strung along the  
guidewire into position at the bifurcation. The distal  
opening of the second guidewire lumen abuts the proximal  
10 strung through the first balloon catheter and out the  
distal opening of the second guidewire lumen. Thus,  
resident in the second bifurcation leg is the second  
guidewire. Then, a second standard stent delivery balloon  
catheter is guided along the second guidewire to a  
15 position within the bifurcation. Typically, expansion of  
both stents can be done one right after the other after  
proper placement of the first and second balloons.

#### Brief Description of the Drawings

20 The foregoing aspects of the invention will be more  
readily understood by reference to the following detailed  
description, taken with the accompanying drawings, in  
which:

25 Figures 1(a) and 1(b) are side views of a stent  
having circumferentially disposed bands wherein the stent  
is in axially unbent and bent positions respectively, the  
latter showing protruding edges;

30 Figures 1(c) and 1(d) are side views of an axially  
flexible stent in accordance with the present invention  
wherein the stent is in unbent and bent positions

5            respectively, the latter displaying an absence of  
         protruding edges;

         Figure 2 is a side view of a portion of the stent of  
Figures 1(c) and 1(d) showing the longitudinal bands,  
10           spaces, and inner radial measurements of bends in the  
         bands being measured in inches;

         Figures 3(a) and 3(b) show a portion of the stent of  
Figure 2 with two bands between two circumferential links  
15           (a) before expansion in the unexpanded state; and (b)  
         after expansion, in the deformed state;

         Figure 4 is a view along the length of a piece of  
cylindrical stent (ends not shown) prior to expansion  
20           showing the exterior surface of the cylinder of the stent  
         and the characteristic banding pattern;

         Figure 5 is an isometric view of a deflection plot  
where the stent of Figure 2 is expanded to a larger  
25           diameter of 5mm;

         Figure 6 shows a two-dimensional layout of the stent  
of Figure 4 to form a cylinder such that edge "A" meets  
edge "B", and illustrating the spring-like action provided  
30           in circumferential and longitudinal directions;

         Figure 7 shows a two dimensional layout of the stent.  
The ends are modified such that the length ( $L_A$ ) is about

5 20% shorter than length ( $L_B$ ) and the width of the band A is greater than the width of band B;

10 Figure 8 shows a perspective view of a stent containing flexible connectors as described in the present invention;

15 Figure 9 shows a stent in which the flexible connectors are attached to stent segments, in layout form. These flexible connectors are attached in an every-other-segment pattern;

20 Figure 10 shows a layout view where the stent segments are connected with a flexible connector in every stent segment pattern;

Figure 11 shows a schematic of the unexpanded stents when loaded on the stent delivery system;

25 Figure 12 shows the stents placed alone;

Figure 13 shows the stents as expanded without the delivery system;

30 Figure 14 shows a modification of the stent in a layout view;

Figure 15 is a plan view of the balloon of the present system;

5                   Figure 16 is an assembly view of the same balloon;

Figure 17 is a view of the balloon when in use;

10                   Figure 18 is a assembly view of another stent which  
may be used on the balloons of Figures 15-17; and

Figure 19 is a plan view of the stent of the previous  
figure.

15                   Detailed Description of Specific Embodiments

20                   Improvements afforded by embodiments of the present  
invention include (a) increased flexibility in two planes  
of the non-expanded stent while maintaining radial  
strength and a high percentage open area after expansion;  
(b) even pressure on the expanding stent that ensures the  
consistent and continuous contact of expanded stent  
against artery wall; (c) avoidance of protruding parts  
during bending; (d) removal of existing restrictions on  
25                   maximum of stent; and reduction of any shortening effect  
during expansion of the stent.

30                   In a preferred embodiment of the invention, an  
expandable cylindrical stent 10 is provided having a  
fenestrated structure for placement in a blood vessel,  
duct or lumen to hold the vessel, duct or lumen open, more  
particularly for protecting a segment of artery from  
restenosis after angioplasty. The stent 10 may be  
expanded circumferentially and maintained in an expanded

5 configuration, that is circumferentially rigid. The stent  
10 10 is axially flexible and when flexed at a band, the  
stent 10 avoids any externally protruding component parts.

10 Figure 1 shows what happens to a stent 10, of a  
similar design to a preferred embodiment herein but  
utilizing instead a series of circumferentially disposed  
bands, when caused to bend in a manner that is likely  
15 encountered within a lumen of the body. A stent 10 with a  
circumferential arrangement of bands (1) experiences an  
effect analogous to a series of railroad cars on a track.  
As the row of railroad cars proceeds around the bend, the  
corner of each car proceeding around the bend after the  
coupling is caused to protrude from the contour of the  
20 track. Similarly, the serpentine circumferential bands  
have protrusions (2) above the surface of the stent 10 as  
the stent 10 bends.

25 The embodiment shown in Figures 1(c) and 1(d) and  
Figure 7 has bands (3) which are axially flexible and are  
arranged along the longitudinal axis. This allows the  
stent to bend so that the bent bands (4) do not protrude  
from the profile of the curve of the stent 10.  
Furthermore, any flaring at the ends of the stent 10 that  
might occur with a stent 10 having a uniform structure is  
30 substantially eliminated by introducing a modification at  
the ends of the stent 10. This modification comprises  
decreasing the spatial frequency and increasing the width  
of the corresponding bands in a circumferential direction

5 (L<sub>A</sub> and A) compared to that of the intermediate section.  
(l<sub>B</sub> and B).

10 In an embodiment of the invention, the spatial  
frequency L<sub>A</sub> may be decreased 0-50% with respect to L<sub>B</sub>, and  
the width A may be increased in the range of 0-150% with  
respect to B. Other modifications at the ends of the  
stent 10 may include increasing the thickness of the wall  
of the stent 10 and selective electropolishing. These  
15 modifications protect the artery and any plaque from  
abrasion that may be caused by the stent 10 ends during  
insertion of the stent 10. The modification also may  
provide increased radio-opacity at the ends of the stent  
10. Hence it may be possible to more accurately locate  
the stent 10 once it is in place in the body.

20 The embodiment as shown in Figures 2 and 6 has the  
unique advantage of possessing effective "springs" in both  
circumferential and longitudinal directions shown as items  
(5) and (6) respectively. These springs provide the stent  
25 10 with the flexibility necessary both to navigate vessels  
in the body with reduced friction and to expand at the  
selected site in a manner that provides the final  
necessary expanded dimensions without undue force while  
retaining structural resilience of the expanded structure.

30

As shown in both Figures 2, 4 and 6, each  
longitudinal band undulates through approximately two  
cycles before there is formed a circumferential link to an  
adjacent band. Prior to expansion, the wave W associated

5 with each of the bands may have approximately the same  
fundamental spatial frequency, and the bands are so  
disposed that the wave W associated with them are  
spatially aligned, so as to be generally in phase with one  
another as shown in Figure 6.

10 The aligned bands on the longitudinal axis are  
connected at a plurality of periodic locations, by a short  
circumferential link to an adjacent band. Consider a  
first common axial position such as shown by the line X-X  
15 in Figures 4 and 6. Here an adjacent pair of bands is  
joined by circumferential link 7. Similarly other pairs  
of bands are also linked at this common axial position.  
At a second common axial position, shown in Figure 6 by  
the line Y-Y, an adjacent pair of bands is joined by  
20 circumferential link 8. However, any given pair of bands  
that is linked at X-X is not linked at Y-Y and vice-versa.  
The X-X pattern of linkages repeats at the common axial  
position Z-Z. In general, there are thus two groups of  
common axial positions. In each of the axial positions of  
25 any one group are links between the same pairs of adjacent  
bands, and the groups alternate along the longitudinal  
axis of the embodiment. In this way, circumferential  
spring 6 and the longitudinal spring 6 are provided.

30 A feature of the expansion event is that the pattern  
of open space in the stent 10 of the embodiment of Figure  
2 before expansion is different from the pattern of the  
stent 10 after expansion. In particular, in a preferred  
embodiment, the pattern of open space on the stent 10



5 before expansion is serpentine, whereas after expansion, the pattern approaches a diamond shape (3a, 3b). In embodiments of the invention, expansion may be achieved using pressure from an expanding balloon or by other mechanical means.

10 In the course of expansion, as shown in Figure 3, the wave W shaped bands tend to become straighter. When the bands become straighter, they become stiffer and thereby withstand relatively high radial forces. Figure 3 shows how radial expansion of the stent 10 causes the fenestrations to open up into a diamond shape with maximum stress being expended on the apices of the diamond along the longitudinal axis. When finite element analyses including strain studies were performed on the stent 10, it was found that maximum strain was experienced on the bands and links and was below the maximum identified as necessary to maintain structural integrity.

25 The optimization of strain of the stent 10 is achieved by creating as large a turn radius as possible in the wave W associated with each band in the non-expanded stent 10. This is accomplished while preserving a sufficient number of bands and links to preserve the structural integrity of the stent 10 after expansion. In an embodiment of the invention, the strain may be less than 0.57 inches/inch for 316L stainless steel. The expansion pressure may be 1.0-7.0 atmospheres. The number of bands and the spatial frequency of the wave W on the longitudinal axis also affect the number of

circumferential links. The circumferential links contribute structural integrity during application of radial force used in expansion of the stent 10 and in the maintenance of the expanded form. While not being limited to a single set of parameters, examples of a stent 10 of the invention having a longitudinal axis and providing axial flexibility of the type shown in Figure 6, may include the following: stents 10 having an expanded diameter of 4mm and a length of 30mm that for example may have about 8-12 rows, more particularly 10 rows; about 6-10 slots, more particularly 8 slots (a slot is shown in Figure 6 as extending between X and Z); and a wave W amplitude of about 1/4-1/10 of a slot length, more particularly 1/8 of a slot length.

The stents described may be fabricated from many methods. For example, the stents may be fabricated from a hollow or formed stainless steel tube that may be cut out using lasers, electric discharge milling (EDM), chemical etching or other means. The stents are inserted into the body and placed at the desired site in an unexpanded form. In a preferred embodiment, expansion of the stent is effected in a blood vessel by means of a balloon catheter, where the final diameter of the stent is a function of the diameter of the balloon catheter used.

In contrast to stents of the prior art, the stent of the invention can be made at any desired length, most preferably at a nominal 30mm length that can be extended or diminished by increments, for example 1.9mm increments.

5

It will be appreciated that a stent in accordance with the present invention may be embodied in a shape memory material, including, for example, an appropriate alloy of nickel and titanium; or stainless steel. In this embodiment after the stent has been formed, it may be compressed so as to occupy a space sufficiently small as to permit its insertion in a blood vessel or other tissue by insertion means, wherein the insertion means include a suitable catheter, or flexible rod. On emerging from the catheter, the stent may be configured to expand into the desired configuration where the expansion is automatic or triggered by a change in pressure, temperature or electrical stimulation.

10

15

20

An embodiment of the improved stent has utility not only within blood vessels as described above but also in any tubular system of the body such as the bile ducts, the urinary system, the digestive tube, and the tubes of the reproductive system in both men and women.

25

In yet a further embodiment, there is described a stent 10 as presently disclosed containing a multiplicity of curvilinear segments 20. These curvilinear segments 20 are connected to each other via a generally perpendicular connector 25. The generally perpendicular connector 25 lies substantially in the plane perpendicular to the longitudinal axis of the stent 10. Each of the stent 10 segments as described herein is connected to an adjacent stent 10 segment. This is done using a series of flexible

30

5 connectors. Importantly, the connectors themselves can be  
made narrower at their midpoints. This enhances the  
possibility of flexure at that point. Of course, it is to  
be realized that alternate designs of the connector to  
insure flexibility are possible, and contemplated by this  
10 invention.

In essence therefore, the stent 10 as described in  
Figure 8 is a stent 10 of considerable flexibility when  
compared to more rigid rectilinear stents. Nonetheless,  
15 the stent 10 of the present invention does not depart from  
the basic concepts set forth herein, in that it discloses  
a continuously curvilinear strut. This curvilinear strut  
is connected to other curvilinear struts via a series of  
"second" more flexible connectors, described above.

20 In any regard, it can be seen that the stent 10 of  
the present invention incorporates various new and useful  
members. One of them is the flexible connector in  
conjunction with a generally curvilinear stent. Another  
25 is the use of the generally larger struts at the ends of  
the stent 10 in order to provide for continued support at  
the stent 10 ends. A final aspect is the use of flexible  
connectors amongst stent 10 segments to provide for  
greater flexibility.

30 In all regards, however, it is to be seen that the  
present invention is to be determined from the attached  
claims and their equivalents.

5 As can be seen from Figures 11 through 14, an  
improved device 100 of the present invention can also be  
made to perform in a bifurcated fashion. In this way, the  
stent 101 contains a central opening 102. This central  
10 opening 102 allows for the passage of an unexpanded stent  
103 of the same size. Typically of course, the two stents  
101,103 will have the same general configuration, and one  
can pass through the other on the same type of diameter  
balloon. In fact, the balloon 150 as seen in the current  
15 figures 11-16 is a bifurcated balloon, but need not be.  
Two separate balloons are certainly capable of performing  
the same function. The balloons are preferably less than  
6 Fr in their unexpanded shape in a preferred embodiment,  
but of course, need not be so constrained.

20 As seen in figures 11-14, the first stent 101 (the  
lower one in the figure) is loaded on one of the balloons  
151. It has an opening 102 central to it. This opening  
faces the upper stent 103 and balloon 152, the upper stent  
102 loaded on the second balloon 152. The upper stent  
25 103, when loaded on the second balloon 152 also has an  
opening 104 which faces the lower stent 101. In this  
fashion, as the second stent 103 is strung through the  
first stent 101, it is placed in such a fashion so as to  
have a mutually facing contact with the first stent 101.  
30 Then, as the balloon and stent combination is guided  
through the human anatomy, the devices will go toward a  
bifurcation. When this happens, the device is caused to  
split using various guide wire techniques. Then, each of  
the respective balloons is inflated.

FIG. 11-16

5

On this inflation, the entire device is expanded such as seen in Figure 13. Thus, the entire bifurcation is covered, and yet in a much easier than typical bifurcated expansions. What is unique is that there is no welding of the stents 101, 103 together, they can be common "off-the-shelf" stents modified only slightly so as to be useful for this particular need.

10

15

It should be noted that the stent of Figures 11-14 can be designed with any slot or wire configurations or of any high density materials or composites and can be balloon expandable or self-expanding or even the combination of both. The devices can be sold separately from separate catheters to be assembled during the desired procedure by the clinicians; can be used with a bifurcated balloon or two separate balloons; or incorporated with one or more radio-opaque markers to allow for better positioning in radio-opacity. The bifurcated stent delivery system is placed by crimping over two balloons and then expanded at the sight of the lesion.

20

25

30

As seen from Figures 15-17, there is described in this present invention a balloon 510, in which is contained a standard balloon catheter 520. These catheters are described in, for instance, U.S. Patent Nos. 5,108,415; 5,156,612 and 5,304,197. Such patents are owned by a common assignee of the present invention, and incorporated herein by reference. Uniquely, however, the current balloon 510 contains a side hole 515 in the

balloon. The side hole 515 is placed at an exit port 516 in the middle 517 of the balloon 510. This side hole 515 creates access to a lumen 525 created in the side of the catheter 510. Thus, this side hole 515 creates an access channel useful for the stent 101 of the current invention.

So in use therefore, the catheter 510 is advanced into the lumen of the artery, as would be typical angioplasty catheter. First, a guidewire 550 is placed within lumen 530 of the catheter 510. Second, the catheter 510 is tracked over the guidewire and into the lumen. Then, the guidewire 550, specially formed for this use is retracted until its tip 555 is placed at the distal marker 535 of the current catheter 516. Then, the guidewire 550 is rotated so that its tip 555 "pops" out of the side hole 515 created in the side lumen 525 of the present catheter 510. The guidewire 550 is then advanced through the side branch artery to give access to the side branch.

In Figures 18-19, the first item described will be the structure of stent 200 in accordance with the invention and illustrated in figures 18-19. The stent 200 is an improvement over other bifurcated stent ideas, in that the stent is continuous through the mid-section 250 of the main branch segment 210, 220. Segment 230 is connected by a weld or other means (such as a pivotable hook or a ball in socket joint) to another section 220 to form the "Y"-shaped stent. Such design will allow for

5 greater vessel coverage at the intersection point of the  
bifurcation.

10 As was mentioned earlier, stent 200 comprises three  
tubular sections (210, 220, and 230) and a continuous  
connection (240). Sections 210, 220, 230 have struts  
211, 221, 231 of sinusoidal shape. Of course, any known  
shape (e.g., straight struts, are possible).

15 The first section (210) is a proximal section  
having as its center axis L. It is intended for  
insertion into main stem of blood vessel for treatment  
upstream of a bifurcation.

20 The first distal section (220) having as its  
section axis L' is at least approximately aligned with  
proximal section 210 prior to use. This first distal  
section 220 is intended for insertion to a blood distal  
branching off from the bifurcation from a proximal blood  
vessel, into which section 210 is to be placed. The  
25 first distal section (220) is attached to proximal  
section 210 by some of the omega-shaped connector  
members 250 seen in Figures 18 and 19. Omega-shaped  
connectors 250, it should be realized, are of different  
shape than struts 211, 221; these omega-shaped  
30 connectors 250 are formed to maximize flexibility, and  
it is to be understood that these struts need not be  
limited to the design disclosed here. It is envisioned  
that other flexible connections are possible.



5           The second distal section (230) having as its axis  
L" is positioned at the side of the first distal section  
220, and has the advantage of being parallel to the  
latter prior to use. The second distal section 230 is  
intended to be inserted into a second distal blood  
10 vessel branching off from the bifurcation.

15           The two distal sections 220 and 230 have their  
proximal ends linked by the connection member 260, which  
is a weld joint comprising elements 261, 262 seen in  
Figure 18. Dowel 261 fits into hole 262 to form weld  
260.

20           Each of section 210, 220, and 230 is preferably  
formed from a tubular component perforated with a  
slotted tubular pattern such that the structure of  
sections 210, 220, 230 allows them to expand along their  
circumferences.

25           In practice section 210, 220, and 230 of stent is  
200 can be manufactured from extruded cylindrical parts  
made of a bendable metal alloy such as 316L stainless  
steel, but may also be made from other known metals such  
as nitinol. The external diameter of sections 210, 220,  
230 typically ranges from 1mm to 4mm prior to use, and  
30 can be expanded further than 2mm and 8mm.

Sections 210, 220 are preferably manufactured from  
a single tubular part in which flexible connectors, such  
as omega-shaped connectors 250 are formed via machining.

5

Weld points 261, 262 are preferably joined by means of, for example, laser welding, or other acceptable alternatives.

10

Furthermore, proximal end 235 of the second distal section 230 may be tapered at the other side of the connector 250. It extends forward in its peripheral area opposite the omega-shaped connectors 250. This tapered portion may also be determined by a plane that is inclined with reference to L' perpendicular to the plane of symmetry of the stent 200.

15

20

After expansion, when the stent 200 is installed at the a bifurcation of the two vessels, distal portion 215 of the proximal section 210 is fit together with the proximal ends 225, 235, of sections 220, 230 of the stent, and ensures maximum coverage of the dilated bifurcation area. This is especially true since weld 260 holds the relative position of sections 220, 230 and the relative positions of sections 210, 220 is set, and covered by omega-shaped connectors 250.

25

30

In this way, once in place, the whole of the grid of the bifurcated stent 200 covers the proximal and distal portions of the two branching vessels and the whole of the dilated bifurcation area.

The stents themselves can be made from any high density material or composite. These stents can be

5 balloon expandable or self-expanding or a combination of both. They can be used on catheters as described herein or on standard catheters.

10 These and other objects of the present invention are accomplished in a stent delivery system which consists of an ingeniously modified angioplasty catheter. Typical angioplasty catheters contain a central lumen useful for stringing a guidewire therethrough. The guidewire then guides the balloon from a point outside the body, along its length, to a point which is about to be stented. The balloon of the angioplasty catheter holds the stent as it is guided through the vasculature. When the obstruction is reached, the balloon is inflated, the stent is similarly inflated, and then the balloon can be deflated. Upon deflation, the balloon can be retracted through the vasculature along the guidewire.

25 In the present invention, a second guidewire lumen is placed at least within the balloon. (It should also be realized that the second guidewire lumen also can readily be placed along a length of the catheter shaft.) This second guidewire lumen is useful for attacking the bifurcated vessel. What occurs, therefore, is the following: a large stent is placed on the balloon so modified. Thereafter, the guidewire is tracked through the body to a point past the obstruction, which for the purposes described herein, is presumed to occur at or near a bifurcation. Onto the guidewire is tracked the modified stent delivery system. The balloon guidewire lumen is

5 placed on to the guidewire outside the body and it is then  
moved along the guidewire to a point inside the body. The  
exit portion of the second balloon guidewire lumen is  
somewhere proximal to the distal end of the balloon, so  
that the entire balloon can be moved to a position along  
10 the vasculature at the obstruction in the body passageway.

When the obstruction is reached, the balloon can be  
inflated. This will usually take care of the "base" and  
one of the "legs" of the bifurcation. When inflated, a  
15 stent which is associated with the stent delivery system  
is similarly inflated. This stent has an opening situated  
along a portion of its wall. This opening is useful for  
opening the second leg of the bifurcated area.

20 The second area is opened in the following manner: a  
second balloon angioplasty catheter, this time containing  
a single basic stent is placed along the guidewire during  
positioning of the balloon catheter. A second guidewire  
is then strung through the catheter to a position where it  
25 emerges from the second opening. Then, the second  
catheter is guided along the second guidewire so that it,  
too, is placed along the second guidewire after the  
guidewire emerges from the distal opening of the balloon  
second guidewire opening. Then, the second catheter can  
30 be inflated when it is resident in the second "leg" of the  
bifurcation. At that point, because the first leg has  
already been expanded and the base of the bifurcation has  
been expanded, once the second leg of the bifurcation is

5 expanded, the entire bifurcation has been attended to and  
the patient is properly stented.

10 Further, there is disclosed a method of stent  
placement which comprises first guiding a guidewire  
through the vasculature. Second, a balloon catheter which  
contains two guidewire lumens is strung along the  
guidewire into position at the bifurcation. The distal  
opening of the second guidewire lumen abuts the proximal  
15 end of the bifurcation. Thereafter, a second guidewire is  
strung through the first balloon catheter and out the  
distal opening of the second guidewire lumen. Thus,  
resident in the second bifurcation leg is the second  
guidewire. Then, a second standard stent delivery balloon  
catheter is guided along the second guidewire to a  
20 position within the bifurcation. Typically, expansion of  
both stents can be done one right after the other after  
proper placement of the first and second balloons.

TOP SECRET